



RB PRINTER FOR SU VACUUM PACKING MACHINES



P/N 1140568

SPECIFICATIONS



Electrical supply: 230 V / 50-60 Hz / 1~
Plug: EU (SCHUKO 2P+G)

Crated dimensions
220 x 355 x 260 mm
Gross weight: 3 kg

SALES DESCRIPTION

- Direct thermal or thermal transfer printer for printing labels.
Specially configured for Sammic SU vacuum packing machines, interface USB-RS232C, to print labels directly from the vacuum packing machine.
- ✓ Print method: Direct thermal / Thermal transfer.
 - ✓ Thermal transfer method is indicated for sous-vide cooking, as thermal transfer labels stand up to 100°C during the cooking process.
 - ✓ 203 dpi resolution.
 - ✓ 8 MB flash memory.
 - ✓ Print speed: 127 mm/s - 5 inch per second.
 - ✓ Code page support.
 - ✓ Emulation options.
 - ✓ User-friendly. Easy maintenance.

OPTIONAL

- ☐ 1140566 Direct thermal labels. ☐ 1140567 Thermal transfer labels.



sammic | www.sammic.com
Food Service Equipment Manufacturer
Polígono Basarte, 1. phone +34 943 15 72 36
20720 Azkoitia, Spain sales@sammic.com



Project	Date
Item	Qty
Approved	

FOOD PRESERVATION AND SOUS-VIDE
ACCESSORIES - VACUUM PACKING MACHINES

product sheet
updated 15/03/2024